



ACTION GRAPHICS

VINYL APPLICATION GUIDE

For your convenience we have produced use this guide for easy trouble-free vinyl graphics fitting. Before you begin you will need the following equipment:

- 1. Tape measure*
- 2. Squeegee*
- 3. A chinagraph or wax pencil*
- 4. A water sprayer*
- 5. Scalpel or pin*

Thoroughly clean the surface area of the vehicle (or other surface) to be worked on.

Using a chinagraph or wax pencil, indicate areas where you intend to position the graphics, for instance, the baseline and centreline.

Spray the surface area where the graphic is to be applied with a thin film of water.

Carefully remove graphic from backing-paper holding only the edges of the application tape.

Apply the graphic aligning it to the position marks made earlier making sure there are no folds or creases.

If the graphic appears to be incorrectly positioned, the water will enable it to be lifted off the surface by a quick release movement.

When satisfied with the position use the squeegee and, starting from the centre of the graphic, smooth firmly onto the surface of the vehicle.

Remove the application tape by carefully pulling it away from the vehicle surface, if the graphic underneath starts lifting with the application tape, smooth it back down firmly and wait until the water has dried sufficiently to allow the graphic to adhere.

Finally, any bubbles that may appear can be eradicated by pricking with a pin or scalpel blade and re-smoothing.

